

TAU1302/TAU1303

Multi-Band GNSS Raw Data Module

Professional

PRODUCT DESCRIPTION

TAU1302/TAU1303 is a high-performance dual-band GNSS raw data module, which is based on the state of art CYNOSURE III architecture. It supports GPS, BeiDou, GLONASS, Galileo, and QZSS.

TAU1302/TAU1303 integrates efficient power management architecture, while providing high precision, high sensitivity and low power GNSS solutions which make it suitable for high precision industries, like precision agriculture, surveying and mapping, deformation monitoring, Unmanned Aerial Vehicle (UAV), etc.



(TAU1302: 16.0x12.2x2.4 mm)



(TAU1303: 7.6x7.6x1.8 mm)

HIGHLIGHTS

- Compact size for high precision industry
- Concurrent reception of multi-band GNSS signals by three RF settings:
 - Option A: L1&L5;
 - Option B: L1&L2;
 - Option C: L1&L6;
- State-of-art low power consumption
- Supports multi-band multi-system high-precision raw data output, easy for 3rd party integration
- Highly integrated module, the best cost-effective high precision GNSS solution


APPLICATIONS



Precision Agriculture



UAV



Deformation Monitoring



Surveying and Mapping

Product selector:

P/N	GNSS							Features							Interfaces				Accuracy			Grade		
	Band (S/D/T)	GPS	BDS	GLONASS	Galileo	NavIC	QZSS	Built-in LNA	Data Logging	D-GNSS	Programmable(Flash)	Raw Data	RTK	Heading	USB	UART	I2C	SPI	Meter	Sub-Meter	Centi-Meter	Standard	Professional	Automotive
TAU1302	D	•	•	•	•		•		•	•	•	•		○	•	○	○			•		•		
TAU1303	D	•	•	•	•		•		•	•	•	•		○	•	○	○			•		•		

○=Supported upon request with special firmware

GENERAL SPECIFICATIONS

GNSS Reception

P/N	RF mode	GPS/QZSS					BDS					GLONASS		Galileo			NavIC
		L1C/A	L1C	L2C	L5	L6	B1I	B1C	B2I	B2a	B3I	L1	L2	E1	E5	E6	L5
TAU1302/TAU1303	A (L1+L5) ^[1]	•	-	-	•	-	•	-	-	•	-	•	-	•	• ^[2]	-	-
	B (L1+L2)	•	-	• ^[3]	-	-	•	-	•	-	-	•	•	•	-	-	-
	C (L1+L6)	•	-	-	-	•	•	-	-	-	•	•	-	•	-	•	-

* [1]: Default mode. Mode B and C are supported through upgrading new firmware.

* [2]: Supports E5a and pilot channel only

* [3]: Supports L2CM

GNSS Engine

Cynosure III GNSS Engine
40 GNSS tracking channels
10Hz maximum update rate

Position Accuracy

GNSS < 1 m CEP

Time to First Fix (TTFF)

Hot start 1 s
Cold start 24 s

Sensitivity

Cold Start -148 dBm
Hot Start -158 dBm
Reacquisition -160 dBm
Tracking & Navigation -162 dBm

Velocity & Time Accuracy

GNSS 0.1 m/s CEP
1PPS 20 ns

Interfaces

UART 1
USB^[4] 1
SPI^[4] 1
I2C^[4] 1

*[4]: Supported upon request with special firmware

Antenna

Active antenna

Operation Limit

Velocity 515 m/s
Altitude 18,000 m

Operating Condition

Main voltage 2.0-3.6 V
Digital I/O voltage 1.8-3.6 V
Backup voltage 1.8-3.6 V

Safety Supervision

Antenna short circuit protection and open circuit detection

Power Consumption

Operating	GPS+QZSS	L1: 22 mA @ 3.3 V
	GNSS	L1+L5: 34 mA @ 3.3 V
	GNSS	L1+L2: 34 mA @ 3.3 V
	GNSS	L1+L6: 34 mA @ 3.3 V
Standby	12 uA	

ENVIRONMENT DATA

Operation temperature -40°C to +85°C
Storage temperature -40°C to +85°C
Certification RoHS, REACH, FCC, CE

PACKAGE

TAU1302	Package: 24 PIN LCC
	Dimensions: 16.0x12.2x2.4 mm
TAU1303	Package: 22 PIN LCC
	Dimensions: 7.6x7.6x1.8 mm

